

Attorney's Docket No.: 324-012192-US (PAR)

PATENT

10/538420

JC17 Rec'd PCT/PTO 08 JUN 2005

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

In re application of: Janne RINNE, et al.

Group No.:

Serial No.:

Filed: HEREWITH

Examiner:

For: TRANSFER OF PACKET DATA IN SYSTEM COMPRISING  
MOBILE TERMINAL, WIRELESS LOCAL NETWORK AND  
MOBILE NETWORK


Commissioner for Patents  
P.O. Box 1450  
Alexandria, VA 22313-1450

TRANSMITTAL OF CERTIFIED COPY

Attached please find the certified copy of the foreign application from which priority is claimed for this case:

Country : PCT  
Application Number : PCT/FI2004/00386  
Filing Date : 24 JUNE 2004

**WARNING:** "When a document that is required by statute to be certified must be filed, a copy, including a photocopy or facsimile transmission of the certification is not acceptable." 37 CFR 1.4(f) (emphasis added.)

  
SIGNATURE OF ATTORNEY

Reg. No.: 44,004

Geza C. Ziegler, Jr.

Type or print name of attorney

Tel. No.: (203) 259-1800

Perman & Green, LLP

P.O. Address

Customer No.: 2512

425 Post Road, Fairfield, CT 06824

NOTE: The claim to priority need be in no special form and may be made by the attorney or agent if the foreign application is referred to in the oath or declaration as required by § 1.63.

(Transmittal of Certified Copy [5-4])

10/538420

Helsinki 18.04.2005

JC17 Rec'd PCT/PTO 08 JUN 2005

ETUOIKEUSTODISTUS  
PRIORITY DOCUMENT

Hakija  
Applicant

1. Nokia Corporation, Helsinki, FI
2. Rinne, Janne, Tampere, FI
3. Haverinen, Henry, Jyväskylä, FI

Kansainvälinen patenttihakemus nro  
International patent application no PCT/FI2004/00386


Kansainvälinen tekemispäivä  
International filing date 24.06.2004

Keksinnön nimitys  
Title of invention

"Transfer of packet data in system comprising mobile terminal, wireless local network and mobile network"

Täten todistetaan, että oheiset asiakirjat ovat tarkkoja jäljennöksiä kansainvälisiä patenttihakemuksia vastaanottavana viranomaisena toimivalle Patentti- ja rekisterihallitukselle alkuaan annetuista selityksestä, patenttivaatimuksista, tiivistelmästä ja piirustuksista sekä niihin tehdyistä korjauksista.

This is to certify that the annexed documents are true copies of the description, claims, abstract and drawing, originally filed with the Finnish Patent Office acting as receiving Office for the international patent applications, and of any corrections thereto.

  
Pirjo Kella  
Tutkimussihteeri

Maksu 50 €  
Fee 50 Eur

Maksu perustuu kauppa- ja teollisuusministeriön antamaan asetukseen 1027/2001 Patentti- ja rekisterihallituksen maksullisista suoritteista muutoksineen.

The fee is based on the Decree with amendments of the Ministry of Trade and Industry No. 1027/2001 concerning the chargeable services of the National Board of Patents and Registration of Finland.

Osoite: Arkadiankatu 6 A  
Address: P.O.Box 1160  
FIN-00101 Helsinki, FINLAND

Puhelin: 09 6939 500  
Telephone: + 358 9 6939 500

Telefax: 09 6939 5328  
Telefax: + 358 9 6939 5328

# HOME COPY

2040759PC/or

1/5

## PCT REQUEST

Original (for SUBMISSION)

0	For receiving Office use only	PCT/FI2004/000386
0-1	International Application No.	
0-2	International Filing Date	24 JUN 2004 (24-06-2004)
0-3	Name of receiving Office and "PCT International Application"	The Finnish Patent Office PCT International Application.
0-4	Form PCT/RO/101 PCT Request	
0-4-1	Prepared Using	PCT-SAFE [EASY mode] Version 3.50 (Build 0002.162)
0-5	Petition The undersigned requests that the present international application be processed according to the Patent Cooperation Treaty	
0-6	Receiving Office (specified by the applicant)	National Board of Patents and Registration (Finland) (RO/FI)
0-7	Applicant's or agent's file reference	2040759PC/or
I	Title of Invention	TRANSFER OF PACKET DATA IN SYSTEM COMPRISING MOBILE TERMINAL, WIRELESS LOCAL NETWORK AND MOBILE NETWORK
II	Applicant	
II-1	This person is	applicant only
II-2	Applicant for	all designated States except US
II-4	Name	NOKIA CORPORATION
II-5	Address	Keilalahdentie 4 FI-02150 Espoo Finland
II-6	State of nationality	FI
II-7	State of residence	FI
III-1	Applicant and/or inventor	
III-1-1	This person is	applicant and inventor
III-1-2	Applicant for	US only
III-1-4	Name (LAST, First)	RINNE, Janne
III-1-5	Address	Piettasenkatu 32 D FI-33580 Tampere Finland
III-1-6	State of nationality	FI
III-1-7	State of residence	FI

2040759PC/or

2/5

## PCT REQUEST

Original (for SUBMISSION )

III-2	Applicant and/or Inventor	
III-2-1	This person is	applicant and inventor
III-2-2	Applicant for	US only
III-2-4	Name (LAST, First)	HAVERINEN, Henry
III-2-5	Address	Einonkuja 10 as. 3 FI-40250 Jyväskylä Finland
III-2-6	State of nationality	FI
III-2-7	State of residence	FI
IV-1	Agent or common representative; or address for correspondence The person identified below is hereby/ has been appointed to act on behalf of the applicant(s) before the competent International Authorities as:	agent
IV-1-1	Name	KOLSTER OY AB
IV-1-2	Address	Iso Roobertinkatu 23, PO Box 148 FI-00121 Helsinki Finland
IV-1-3	Telephone No.	+358-9-618 821
IV-1-4	Facsimile No.	+358-9-602 244
IV-1-5	e-mail	kolster@kolster.fi
V	DESIGNATIONS	
V-1	The filing of this request constitutes under Rule 4.9(a), the designation of all Contracting States bound by the PCT on the international filing date, for the grant of every kind of protection available and, where applicable, for the grant of both regional and national patents.	
VI-1	Priority Claim	NONE
VII-1	International Searching Authority Chosen	Swedish Patent Office (ISA/SE)

2040759PC/or

3/5

**PCT REQUEST**

Original (for SUBMISSION )

VIII	Declarations	Number of declarations	
VIII-1	Declaration as to the identity of the inventor	-	
VIII-2	Declaration as to the applicant's entitlement, as at the international filing date, to apply for and be granted a patent	1	
VIII-3	Declaration as to the applicant's entitlement, as at the international filing date, to claim the priority of the earlier application	-	
VIII-4	Declaration of inventorship (only for the purposes of the designation of the United States of America)	-	
VIII-5	Declaration as to non-prejudicial disclosures or exceptions to lack of novelty	-	

2040759PC/or

4/5

## PCT REQUEST

Original (for SUBMISSION )


VIII-2-1	<b>Declaration: Entitlement to apply for and be granted a patent</b> Declaration as to the applicant's entitlement, as at the international filing date, to apply for and be granted a patent (Rules 4.17(ii) and 51bis.1(a)(ii)), in a case where the declaration under Rule 4.17(iv) is not appropriate: Name (LAST, First)	<b>in relation to this international application</b>  NOKIA CORPORATION is entitled to apply for and be granted a patent by virtue of the following:
VIII-2-1(i)		NOKIA CORPORATION is entitled as employer of the inventor, RINNE, Janne
VIII-2-1(i)		NOKIA CORPORATION is entitled as employer of the inventor, HAVERINEN, Henry
VIII-2-1(i)	This declaration is made for the purposes of:	all designations except the designation of the United States of America

2040759PC/or

5/5

## PCT REQUEST

Original (for SUBMISSION)

IX	Check list	number of sheets	electronic file(s) attached
IX-1	Request (including declaration sheets)	5	✓
IX-2	Description	14	-
IX-3	Claims	5	-
IX-4	Abstract	1	✓
IX-5	Drawings	2	-
IX-7	TOTAL	27	
	Accompanying Items	paper document(s) attached	electronic file(s) attached
IX-8	Fee calculation sheet	✓	-
IX-9	Original separate power of attorney	✓	-
IX-11	Copy of general power of attorney	✓	-
IX-17	PCT-SAFE physical media	-	✓
IX-19	Figure of the drawings which should accompany the abstract	3	
IX-20	Language of filing of the International application	English	
X-1	Signature of applicant, agent or common representative		
X-1-1	Name	KOLSTER OY AB	
X-1-2	Name of signatory	by 	Tapio Valkeiskangas
X-1-3	Capacity		

## FOR RECEIVING OFFICE USE ONLY

10-1	Date of actual receipt of the purported International application	24 JUN 2004 (24-06-2004)
10-2	Drawings:	
10-2-1	Received	
10-2-2	Not received	
10-3	Corrected date of actual receipt due to later but timely received papers or drawings completing the purported International application	
10-4	Date of timely receipt of the required corrections under PCT Article 11(2)	
10-5	International Searching Authority	ISA/SE
10-6	Transmittal of search copy delayed until search fee is paid	

## FOR INTERNATIONAL BUREAU USE ONLY

11-1	Date of receipt of the record copy by the International Bureau	
------	--	--

## **TRANSFER OF PACKET DATA IN SYSTEM COMPRISING MOBILE TERMINAL, WIRELESS LOCAL NETWORK AND MOBILE NETWORK**

### **BACKGROUND OF THE INVENTION**

5 The invention relates to the transfer of packet-switched data in a system comprising a mobile terminal, a wireless local network and a mobile network.

Packet-switched data transmission services have been developed for mobile terminals. GPRS services (General Packet Radio Service) are widely used in terminals supporting the GSM radio technology and packet-switched services of the 3GPP system (Third-Generation Partnership Project) based on the WCDMA (Wideband Code Division Multiple Access) radio technology are also based on GPRS. PDP contexts are generally logical connections on which IP data are transferred from a mobile station to a boundary node (GGSN) in a GPRS/3GPP network and vice versa. Different PDP contexts may be provided with different quality of service (QoS) properties, thereby enabling optimal transmission of time-critical or error-critical data, for instance. In addition, an IP multimedia subsystem IMS is designed in the 3GPP system for providing various IP multimedia services to 3GPP mobile stations (UE; User Equipment). The IMS utilizes PDP contexts for data transfer to or from a mobile station. The IMS includes functions that enable the negotiation of an end-to-end session on the application plane using the SIP protocol (Session Initiation Protocol), the features of the session being for instance the codecs used, the termination points and the quality of service (QoS). For arranging the negotiated end-to-end quality of service also in the 3GPP network, a service based local policy (SBLP) is applied. The IMS includes a call session control function (CSCF), which includes a PDF function (Policy Decision Function) for authorizing quality of service resources (bandwidth, delay, etc.) for an IMS session based on SIP-layer SDP information (Session Description Protocol).

30 Besides access via the conventional access networks of the PLMN (Public Land Mobile Network) networks, such as the BSS (Base Station Subsystem) of the GSM, a need has also risen to allow access to the services of a PLMN by local networks primarily targeted at providing high speed data transmission in a limited area, such as in an office building. WLAN (Wireless Local Area Network) technologies are very popular today and standardization work has been done in 3GPP to define WLAN-3GPP interworking. This interworking



may include the usage of 3GPP subscriber management procedures, such as authentication and charging procedures, as well as data transmission via the 3GPP core network for mobile terminals in a WLAN network. The basic concept is to provide a 3GPP subscriber with access via a WLAN network, also  
5 when roaming abroad. 3GPP specification TS 23.234 "3GPP system to Wireless Local Area Network (WLAN) interworking", version 6.0.0, March 2004, defines the system description for WLAN-3GPP interworking.

For WLAN interworking, the 3GPP network is provided with some new network elements or entities. A WLAN Access Gateway (WAG) is a gateway via which the data to/from the WLAN Access Network is transferred to  
10 provide the MS with 3G PS based services. A Packet Data Gateway (PDG) is a network element providing access for WLAN roaming mobile terminals to external IP networks, including those supporting 3GPP PS (Packet-switched) domain-based services. An AAA (Authentication, Authorization and Accounting) server may provide authentication and charging services for WLAN roaming  
15 mobile terminals.

It is desirable that end-to-end QoS negotiation also be provided for mobile terminals roaming in WLAN networks. The above-mentioned 3GPP specification TS 23.234 defines on page 29 that the PDG performs the functions of a service-based local policy enforcement point (PEP) and communicates with a policy decision function to allow a service-based local policy. QoS interworking information may be obtained from the policy decision function. IETF RFC (Request For Comments) 2753 "A Framework for Policy-based Admission Control", R. Yavatkar et al., January 2000, describes a framework for  
20 providing policy-based control and a client-server protocol for communication between a policy server (PDP; Policy Decision Point) and its client (PEP). However, the 3GPP specification TS 23.234 does not disclose how to arrange the adoption of the policy for the terminal in the WLAN-3GPP interworking system.

## 30 BRIEF DESCRIPTION OF THE INVENTION

The object of the invention is thus to provide a method and equipment for implementing the method so as to enable an enhanced data transfer method for terminals visiting a wireless local network. The objects of the invention are achieved by a method, a system, a network element, a wireless terminal,  
35 and computer programs, which are characterized by what is stated in the independent claims. Some preferred embodiments are disclosed in the de-

pendent claims.

According to an aspect of the invention, end-to-end service related parameters are signalled via a separate signalling element. A resource authorization identifier is received in the mobile terminal from the signalling element. The resource authorization identifier is transmitted to the mobile network via the local network. Authorization is requested from the signalling element by the mobile network on the basis of the resource authorization identifier. A tunnel between the mobile terminal and the mobile network is bound to the end-to-end data flow of the mobile terminal on the basis of an authorization response received from the signalling element and comprising identification information on the end-to-the end data flow and tunnel identification information identifying the tunnel.

The advantage of the invention is that a policy authorized by a signalling element, such as a SIP end-to-end quality-of-service negotiation signalling element, may be used in a system in which the mobile terminal accesses the mobile network via a wireless local network. Thus, it is possible to arrange a service in the local system comprising the mobile network and the wireless local network on the basis of a confirmation from the signalling element. By the authorization, it is possible to achieve mapping between the data flow in the system of the mobile network and the wireless local network and the end-to-end data flow.

In one embodiment, the authorization may comprise information on the allowed quality of service, and the underlying data transmission resources in the system are adapted according to this QoS information.

## BRIEF DESCRIPTION OF THE FIGURES

In the following, some preferred embodiments of the invention will be described in detail with reference to the accompanying drawings, in which

Figure 1 generally illustrates a WLAN-3GPP interworking system;

Figure 2 shows the WLAN-3GPP interworking protocol architecture;

and

Figure 3 is a flow diagram of an embodiment of the invention.

## DETAILED DESCRIPTION OF THE INVENTION

The method of an embodiment is illustrated next with reference to an exemplary WLAN-3GPP interworking system shown in Figure 1. However, the invention is applicable to any packet-switched telecommunication system

for mobile terminals visiting wireless local networks. Besides a system incorporating a 3GPP network, the method of the invention is applicable to a system in accordance with a second-generation GPRS service, for instance. The local network is, in accordance with an embodiment, a wireless local area network  
5 employing user authentication and network access control according to an IEEE 802.1x standard, such as a wireless local area network according to the IEEE 802.11i standard. However, the invention can also be applied to a system comprising another IEEE 802-based wireless local area network or some other type of local networks, typically to networks operating at un-licensed frequency bands, such as a network according to the BRAN (Broadband Radio  
10 Access Networks) standard, a Home RF network or a Bluetooth network. The BRAN standards comprise High Performance Radio Local Area Network HIPERLAN standards of types 1 and 2, HIPERACCESS and HIPERLINK standards.

15 Reference is made to Figure 1, wherein the main parts of a mobile system include a WLAN access network AN, a 3GPP network part PLMN comprising network elements for WLAN interworking, and a mobile station MS, also called user equipment UE in 3GPP specifications. It is to be noted that the WLAN-3GPP interworking specification work is not finished at the time of filing  
20 of the present application, and the basic principles of the present invention can also be applied to modified WLAN-3GPP interworking systems.

The WLAN access network AN and the 3GPP network PLMN can communicate over an IP-based (Internet Protocol) network (IPNW). As shown in Figure 1, the WLAN access network AN can operate as a UMTS access  
25 network, and it can also provide access to other networks, such as the public Internet. The WLAN access network AN comprises access elements called access points AP, which provide a mobile station MS with radio access and thus terminate the broadband radio connection. The access point AP controls the L2 radio interface according to the applied radio technology, which means the  
30 IEEE 802.11 standard according to one embodiment. The IEEE 802.11 specifications determine both physical-level and MAC-level protocols for data transmission over the radio interface. The data transmission can utilize either infrared or two spread-spectrum techniques (Direct Sequence Spread-Spectrum DSSS, Frequency Hopped Spread-Spectrum FHSS). Both spread-spectrum  
35 techniques utilize a 2.4 GHz band. The MAC layer utilizes a CSMA/CA (Carrier Sense Multiple Access with Collision Avoidance) technique. The AP also man-

ages the bridging of data streams at the radio interface or the routing thereof to and from other network nodes. It is to be noted that instead of a physical access point, WLAN base station, the term access point AP may also refer to a logical WLAN access point which may be accessed by a number of WLAN  
5 base stations. The WLAN access network AN may also comprise further WLAN related network elements, such as a control element or a gateway element GW.

The 3GPP network PLMN may comprise a UMTS terrestrial radio access network UTRAN and a UMTS core network CN, or at least some functionality thereof (not shown in Figure 1). The following describes network elements related to WLAN-3GPP interworking. The 3GPP network PLMN comprises an Authentication, Authorization and Accounting (AAA) server AS, which may provide authentication services and preferably also charging services. Therefore, 3GPP network subscriber data and authentication services can be  
15 used for mobile stations MS roaming in the WLAN network AN and comprising a UMTS subscriber identity module USIM and/or a (GSM) SIM. A mobile station MS user does not necessarily have to have a contract made in advance with the WLAN network AN operator. In such a case, an MS can be charged for the wireless connection provided by the WLAN network AN later on via the  
20 PLMN. Even though the AAA server AS is shown as a separate element in Figure 1, it can be implemented as part of a PLMN network element. A HLR/HSS (Home Location Register/ Home Subscriber Server) located within the 3GPP subscriber's home network is the entity containing the authentication and subscription data required for the 3GPP subscriber to access WLAN interworking services. The HLR/HSS includes for example information on the  
25 quality of service allowed to a subscriber (user profile) and information for the use of services provided by the IMS. The AS communicates authorization information to WLAN and maintains information on the status of the WLAN mobile stations MS.

30 If the PLMN is not the home network (HPLMN) of the mobile station MS, i.e. the mobile station MS is roaming in the PLMN, the roamed network must communicate with the HPLMN for purposes of authentication and charging. The HPLMN comprises the HLR/HSS, and typically also an authentication centre AuC calculating authentication vectors. An AAA proxy may relay information between the WLAN and the AAA server AS and carry out subscriber  
35 management-related actions in the roamed network. Figure 1 does not show

any other HPLMN elements, such as the 3GMSC or the SGSN, via which the connection to the HLR/AuC is typically set up. The 3GPP specifications also refer to the roamed network as a serving network (SN) and to the HPLMN as merely a home network (HN).

5           A packet Data Gateway PDG is a network element providing access for WLAN roaming mobile stations MS to external IP networks, including those supporting 3GPP PS Domain based services. The packet data gateway PDG operates as a gateway between the packet radio system of the UMTS network and an external packet data network PDN. External data networks include for  
10 instance the UMTS or GPRS network of another network operator, the Internet or a private local area network.

The mobile station MS may be a mobile phone, a table computer with a WLAN radio interface adapter, or a PDA device, for instance. There may be mobile stations MS of different classes according to their capabilities. The  
15 MS may support data transfer via the WLAN access network AN, UTRAN, and/or some other network such as the BSS of GSM, even substantially simultaneously. The mobile station MS is equipped with an IC card including a (U)SIM utilized by a 3GPP subscriber to access the WLAN network for 3GPP interworking purposes.

20           The WLAN Access Gateway WAG is a gateway via which the data to/from the WLAN Access Network AN is transferred to provide the MS with 3G PS based services. The WLAN Access Gateway resides in the VPLMN in the roaming case, and in the HPLMN in the non-roaming case. The WAG allows a visited 3GPP network PLMN to generate charging information for users ac-  
25 cessing via the WLAN AN in the roaming case, enforces the routing of packets through the PDG, performs collection of per tunnel accounting information, and filters out packets based on unencrypted information in the packets. The WAG will forward packets only if they are part of an existing tunnel or expected mes-  
sages from the MS (service requests and tunnel establishment messages).

30           For a more detailed description of various WLAN/3GPP interworking related network elements, reference is made to 3GPP specification TS 23.234, v. 6.0.0, "3GPP to Wireless Local Area Network (WLAN) interworking, System description (Release 6)", March 2004.

A 3GPP packet data system may also comprise many other func-  
35 tions, such as a service control function SCF for intelligent network services, and a charging gateway CGF attending to charging. According to an embodi-

ment, the WLAN-3GPP interworking system supports at least some IMS related features. Figure 1 illustrates a call session control function CSCF, which may have three different roles: Proxy-CSCF (P-CSCF) which comprises a PDF function and transfers SIP messages to other SIP network elements; Interrogating-CSCF (I-CSCF) which is a subscriber home network contact point and determines the serving CSCF (S-CSCF) and forwards SIP requests to the S-CSCF; S-CSCF which is a CSCF controlling the end-to-end session of a mobile station. For a more detailed description of the conventional IMS system features, reference is made to 3GPP specification 3GPP TS 23.228, v.6.5.0 (March 2004), *'IP Multimedia Subsystem (IMS); Stage 2; Release 6'*. A suitable method for session establishment and QoS selection in the WLAN-3GPP interworking system utilizing IMS principles is illustrated later in connection with Figure 3.

To obtain the packet-switched services of the WLAN network AN, the mobile station MS has to perform a WLAN technology-specific access procedure, making the location of the MS known at the selected WLAN network AN. In the case of an IEEE 802.11 network, the MS performs an association procedure. The MS is then able to communicate with an access point AP of the WLAN network. PLMN network selection for the MS may be carried out. Network selection and advertisement procedures are described in Chapter 5.4 of the 3GPP TS 23.234. An authentication procedure may be initiated by the MS by sending a network access identifier (NAI) to the WLAN AP which determines the correct (home) AAA server AS and forwards the authentication request to the correct AAA server AS. The WLAN authentication and authorization by the 3GPP AAA server involves the use of an EAP (Extensible Authentication Protocol) Authentication and Key Agreement (AKA) procedure. The WLAN mobile station MS uses the NAI as identification towards the 3GPP WLAN AAA server AS. In this procedure, the subscriber identity module (SIM) information and corresponding information in HLR may be used. If the authentication is successful, the MS may register as a WLAN user to the 3GPP network PLMN. More details on WLAN access and authorization are described in Chapter 7.2 of the 3GPP TS 23.234 specification.

To receive and transmit packet-switched data, a registered mobile station MS has to activate at least one tunnel. This makes the MS known to the PDG and creates a logical data transfer context at the mobile station MS, the WAG and the PDG. The protocol stack between the MS and the PDG is illus-

trated in Figure 2. When the tunnel is being established, a remote IP address identifying the mobile station MS, which could be an IPv4 or IPv6 address, is defined for the MS. A local IP address of the MS identifies the WLAN MS in the WLAN AN, i.e. the local IP address is used at the Transport IP layer. The remote IP address can be assigned by the home-PLMN, visited-PLMN or an external IP network. In addition to other tunnel related data, such as the negotiated QoS profile, the remote IP address is defined in tunnel information maintained by the PDG.

The tunnel establishment is not coupled to WLAN access authentication/authorization. The WLAN UE may establish several tunnels in order to access several external IP networks simultaneously. External IP network selection is performed as part of the establishment of each tunnel, and the mobile station MS may indicate a preferred WLAN access point name (W-APN).

According to an embodiment, in order to implement a service-based local policy in the WLAN-3GPP interworking system, the PDG comprises a PEP function (Policy Enforcement Point) similar to that of the 3GPP IMS system. However, there are no PDP contexts and associated mechanisms (as those available for GPRS terminals) for roaming WLAN terminals connecting to the PDG via a WLAN network and the WLAN access gateways. Thus, the policy adoption arrangement in the present WLAN-3GPP interworking system differs from that for GPRS terminals. The PEP function controls the offering of quality-of-service resources to the data flow according to the authorization received from the PDF. For binding the authorization decision, the PDF creates a resource authorization identifier, which may be referred to as an authorization token as in the IMS system, for the session and transmits it to the mobile station MS. When the tunnel is being established, the mobile station MS is configured to send to the PDG an authorization token and at least one flow identifier that constitute binding information. The flow identifier identifies the IP media flow associated with the SIP session. There may be a flow identifier for each media component that is to be transferred end to end. The PDG requests authorization for allocating resources to the session indicated by the binding information from the PDF, which is located at the P-CSCF (Proxy CSCF). The PDF functionality makes a final decision on resource allocation to the session and responds to the PDG.

On the basis of the authorization from the PDF, the PDG arranges binding for the external data flow to a tunnel between the MS and the PDG.

The gating/filtering functionality offered by the PEP thus tends to identify a given flow or a group of flows by including information about possible header fields in the form of a set of packet filter parameters, i.e. packet filters. The PEP may be arranged to directly map the data flows received from external  
5 networks into the correct tunnels on the basis of the packet filters, one or more packet classification parameters (e.g. destination gate/source IP address) being specified in a packet filter. The packet filter(s) may be completely defined, when establishing the logical application-plane connection for the data flow, from identifying identifiers at the P-CSCF element (PDF function), and transferred to the PDG (PEP function). The PEP function may determine a gate by  
10 the packet filters for the data flow which it binds to at least one tunnel based on a tunnel identifier. Packet filters could be tunnel-specific, whereby each packet filter is bound to one tunnel.

Figure 3 shows a signalling diagram illustrating in more detail the  
15 establishment or modification of a tunnel between the MS and the PDG when applying a service-based local policy in accordance with a preferred embodiment of the invention. The P-CSCF receives 301 a SIP SDP message including the necessary information about the application-plane session to be set up, such as termination points and the bandwidth requirement. The message 301  
20 may originate for instance from another CSCF element (S-CSCF) because of a session invite request from another party to the application-plane logical connection or the mobile station MS. The PDF function authorizes the quality of service resources (bandwidth, delay, etc.) for the IMS session based on the SDP information. The PDF creates an authorization token for the session and  
25 sends 302 the authorization token in an SDP message to the mobile station MS. For a more detailed description of the communication between the P-CSCF (PDF) and the mobile station MS, reference is made to 3GPP specification 3GPP TS 23.207, v. 6.2.0, *'End-to-End QoS Concept and Architecture; Release 6'*.

30 In one embodiment, the mobile station MS comprises a translation/mapping function adapting 303 the application-plane (or IP-plane) quality of service requirements to the WLAN-3GPP interworking system quality of service parameters, i.e. it specifies the QoS parameters to be requested for the tunnel for user data transmission. When the tunnel is being established, the  
35 mobile station MS sends 304 to the selected PDG a tunnel establishment or modification request including not only the conventional data of a tunnel estab-



lishment request but also an authorization token and at least one flow identifier, in one embodiment the tunnel identifier. In an alternative embodiment, the mobile station MS does not itself adapt the QoS requirements but the network, preferably the PDG, does the adaptation. In this embodiment, the tunnel establishment message 304 does not specify any MS determined QoS parameters. In a further embodiment, no QoS requirement information is sent from the MS but the PDG determines the QoS on the basis of the authorization from the PDG.

The PDG receives the request 305 and determines the appropriate P-CSCF (PDF) on the basis of the authorization token. The PDG transmits 306 a request to authorize the required resources to the PDF functionality of the P-CSCF indicated by the authorization token. This request comprises the binding information. When the PDF of the P-CSCF finds the IP flow information corresponding to the request 306, it makes the final decision about allocating resources to the session. The PDF transmits 307 a response including the policy to the PDG. The authorization response includes an authorization token, at least one packet classification parameter (packet classifier) negotiated on the application plane and intended as the filter, and QoS information (maximum QoS). In one embodiment, other information similar to that of the Go interface between the CSCF and the PDG in 3GPP specification 3GPP TS 23.207, v. 6.0.0 *'End-to-End QoS Concept and Architecture (Release 6)'* may also be used.

The PDG typically responds 308 to the decision message 307. If the PDF allows resource allocation, the PDG may then bind the information in the authorization response to an identifier referring directly or indirectly to a tunnel, i.e. to a tunnel already existing or being established between the MS and the PDG. The tunnel between the mobile terminal and the mobile network is thus bound to the end-to-end data flow of the mobile terminal on the basis of the authorization response received 307 from the signalling element and comprising identification information on the end-to-end data flow (for instance the source IP address) and tunnel identification information identifying the tunnel. The PDG can thus arrange a tunnel between the MS and the PDG provided with properties in accordance with the authorization 307 and the request 304. The PDG may check, based on the quality of service information received from the PDF, that the quality of service requested for the tunnel does not exceed the quality of service negotiated on the application plane and authorized by the

PDF. In one embodiment, the PDG comprises a translation/mapping function which adapts the authorized QoS information to appropriate QoS parameters in the WLAN-3GPP interworking system. Underlying WLAN and/or 3GPP connection resources may be reserved (309) in accordance with the quality of service adapted by the WLAN-3GPP interworking system, preferably by the PDG, from the quality of service parameters of the IP plane or application plane of the mobile station MS (unless the PDG has had to restrict the requested quality because of subscriber data or its own resource limitations, for example). Based on the response 307, the PDG (PEP function) may in one embodiment generate 309 a logical gate, which implements access control according to the decision of the PDF based on the at least one packet classification parameter obtained from the PDF as its packet filter parameter for one or more tunnels to the MS. The packet classifier may be based on the IP-address and port number, for instance. The gate is bound 309 to the tunnel being established based on a (tunnel) identifier distinguishing it from other tunnels. Other information received from the PDF may also be stored in the PDG.

In one embodiment, the PDG sends a response 310 to the WAG; however, such response may be not necessary. The PDG may transmit information (possibly via the AAA proxy) for arranging filtering in the WAG according to the policy authorized by the PDF. The WAG may arrange filtering based on this information. The WAG may initiate the establishment of a radio network service, whereby a new WLAN-3GPP bearer is set up or modified 311 for the mobile station MS. If the requested QoS attributes cannot be provided for instance on the basis of the subscription, the WAG informs this to the PDG, which confirms new QoS attributes. The WAG sets the packet flow identifier and the radio priority in accordance with the negotiated QoS and responds 312 to the mobile station MS. In an alternative embodiment, the QoS resources are arranged locally in the WLAN network AN on the basis of the information from the PDG. For instance, the QoS may be arranged locally by WSM (Wi-Fi Scheduled Multimedia) being specified for IEEE 802.11e WLAN technology.

The mobile station MS updates its connection information with the tunnel and the WLAN-3GPP bearer. The MS is now able to send and receive data packets of the logical connection negotiated on the application plane and use the tunnel. After step 312, an application of the mobile station MS or the entity reserving quality of service for it is still able to send the necessary messages to finally activate the end-to-end session. For example, an application

using the RSVP protocol may send and receive RSVP path and RSVP response messages, based on which the underlying WLAN-3GPP interworking system transmission resources can also be updated. Besides the above-described features, other features may be performed in the WLAN-3GPP interworking system during tunnel establishment/modification. As an example, the PDG contacts the AAA server AS for authorization of the MS.

The PDG is then able to transfer received downlink packets fulfilling the filter conditions defined for the gate to the mobile station using the tunnel that is associated with the gate. When a packet is received 313 from an external packet data network, its header fields are checked 314. When doing this, the PDG compares the header fields of the packets received from the external IP network PDN with the packet classifiers of the gates, based on which the PDG knows if the packets can be forwarded to the terminal, and, if so, which tunnel is to be applied to each IP packet. If a gate is found, whose packet classifiers the packet corresponds to, i.e. the header fields of the packet correspond to the set of packet classification parameters determined by the PDF at the PDG (PEP function), the PEP determines the identifier of the tunnel associated with the gate and directs 315 the packet to be transferred in accordance with the tunnel and the underlying WLAN network resources defined therein. If the packet identifiers do not conform to the filter conditions bound to the tunnel, the packet cannot be transferred by means of the tunnel. It is to be noted that the messages illustrated in Figure 3 are only one example of arranging the data transmission and the ongoing 3GPP-WLAN development work may lead to another kind of network structure/signalling arrangement.

The features illustrated in association with Figure 3 can also be utilized such that the tunnel arranged for signalling connectivity to the P-CSCF is also utilized for user data transmission between the MS and the PDG, whereby no tunnel establishment messages are required but instead messages of other type may be used between the MS and the PDG. In another embodiment, a first tunnel between the mobile station MS and a first network element (PDG) of the mobile network is established for end-to-end service parameter signalling (via the P-CSCF), and a second tunnel between the mobile station MS and a second network element of the mobile network (another PDG) is established for user data transmission after the reception of the (resource authorization) identifier.

The applicability of the functions illustrated above are not limited to

any specific tunnelling technique. In one embodiment, tunnels are IPsec tunnels and identified by at least one IPsec tunnel specific identifier which may be used when binding authorization (and the classification parameters thereof) to the tunnel and when arranging underlying data transmission resources.

5           In this embodiment, the IPsec tunnel may be established between the MS and the PDG by utilizing the IKE (Internet Key Exchange) protocol. First the MS and the PDG perform a key exchange by Diffie-Hellman procedure and generate an IKE security association. In one embodiment, the IKE security association is authenticated by using an EAP (Extensible Authentication Protocol) SIM or EAP AKA (Authentication and Key Agreement) procedure. After this, separate security associations are negotiated for user traffic. These associations are referred to as CHILD SAs. In the present embodiment, the SIP signalling could have a specific CHILD AS, and no policy control would be needed for the SIP signalling. Thus, the token could be transferred to the mobile station (step 302 in Figure 3) by a payload packet protected by the IPsec using the CHILD AS. In one embodiment, the token transferred from the mobile station MS to the PDG is included in a field of a CREATE CHILD AS negotiation message used for negotiating security association between the MS and the PDG. One or more new data fields can be reserved in these messages for transferring the token. In another embodiment, INFORMAL negotiation of the IPsec is used to deliver the parameters required for arranging the policy control by the PDG. These parameters can be associated with an earlier negotiated CHILD SA which could be the one already negotiated for the SIP session.

25           Thus, the token could be bound to a CHILD AS security association identified by an SPI (security parameter index) and possibly with the mobile station's and/or PDG's IP address. This SPI is also included in user-plane packets of the IPsec ESP (encapsulating security payload) or AH protocols.

30           In an embodiment, different media types/components, typically audio, video and data, are allocated with different flow identifiers. In this embodiment, the mobile terminal MS may in step 303 generate the flow identifiers for the media types. The request for establishing/modifying the tunnel may thus comprise more than one flow identifier possibly relating to the same token. With this embodiment, it is possible to separate different media types and even reserve different QoS for different media types.

35           In one embodiment, the tunnel and/or underlying connection reser-

vations may also be modified later. The features illustrated above are applicable between the MS and PDGs in the home PLMN or in visited PLMN.

In an alternative embodiment differing from Figure 3, the authorization token is sent using an already established tunnel, i.e. the end-to-end QoS  
5 adaptation based on the authorization of the PDF is separate from the tunnel establishment procedure and the data transmission resources in WLAN network AN and/or the PLMN may be adapted according to the authorization.

It is to be noted that the authorization identifier from the PDF may be some other identifier than the authorization token or that the authorization  
10 token may differ in contents from that for GPRS services. Further, for non-session based applications some binding information may be used.

The invention can be implemented in a mobile station and in network elements (in an embodiment, in the mobile station MS and in the PDG) by respective computer program codes executed in a processor of the respective device. Computer program codes can be received via a network and/or be  
15 stored in memory means, for instance on a disk, a CD-ROM disk or other external memory means, from which they can be loaded into the memory of the processing device. Hardware solutions or a combination of software and hardware solutions may also be used. A chip unit or some other kind of module for  
20 controlling the network element (or the mobile station MS) may in one embodiment cause the device to perform the inventive functions in the network element (or the mobile station MS).

It is obvious to a person skilled in the art that as technology advances, the basic idea of the invention can be implemented in a variety of  
25 ways. The invention and its embodiments are thus not limited to the above examples, but may vary within the claims. Different features may thus be omitted, modified or replaced by equivalents.

## CLAIMS

1. A method of arranging transmission of packet data in a system comprising a mobile terminal, a wireless local network and a mobile network, arranging data transmission between the mobile terminal and the  
5 wireless local network, **characterized** by  
    signalling end-to-end service related parameters via a separate signalling element,  
    receiving a resource authorization identifier in the mobile terminal from the signalling element,  
10      transmitting the resource authorization identifier to the mobile network via the local network,  
    requesting authorization from the signalling element by the mobile network on the basis of the resource authorization identifier, and  
    binding a tunnel between the mobile terminal and the mobile network to an end-to-end data flow of the mobile terminal on the basis of an authorization response received from the signalling element and comprising identification information on the end-to-end data flow and tunnel identification information identifying the tunnel.  
15
- 20      2. A method as claimed in claim 1, **characterized** by  
    transmitting at least one filter or gate parameter from the signalling element to the mobile network,  
    associating the received at least one filter or gate parameter with the tunnel, and  
25      arranging filtering or gating in the mobile network to/from the tunnel based on the association.
3. A method as claimed in claim 1 or 2, **characterized** in that the same tunnel between the mobile network and a network element of the  
30 mobile network and utilizing the data transmission resources of the local network is used for signalling purposes and for user data transmission.
4. A method as claimed in claim 1 or 2, **characterized** in that a first tunnel between the mobile terminal and a first network element of the  
35 mobile network is established for end-to-end service parameter signalling, and a second tunnel between the mobile terminal and a second network element of

the mobile network is established for user data transmission after the reception of (resource authorization) identifier.

5           5. A method as claimed in any one of the preceding claims, **characterized** in that the tunnel between the mobile terminal and the mobile network is an IPSec tunnel, whereby the tunnel is established by utilizing an IKE (Internet Key Exchange) protocol.

10           6. A method as claimed in any one of the preceding claims, **characterized** in that  
the mobile network is a 3GPP network offering a packet-switched service comprising at least one network element supporting access via a WLAN (Wireless Local Area Network).

15           7. A method as claimed in claim 5, **characterized** by  
arranging an association between the tunnel and a 3GPP-WLAN interworking system bearer.

20           8. A wireless system comprising a mobile terminal, a wireless local network and a mobile network, wherein the wireless local network is arranged to provide data transmission for the mobile terminal, **characterized** in that

the mobile terminal is arranged to receive a resource authorization identifier from a separate signalling element during the negotiation of end-to-end service related parameters,

25           the mobile terminal is arranged to transmit the resource authorization identifier to the mobile network via the local network,

the mobile network is arranged to request authorization from the signalling element on the basis of the resource authorization identifier,

30           the mobile network is arranged to bind a tunnel between the mobile terminal and the mobile network to an end-to-end data flow of the mobile terminal on the basis of an authorization response received from the signalling element and comprising identification information on the end-to-end data flow and tunnel identification information identifying the tunnel.

35           9. A network element for a mobile network connectable to a wireless

local network providing data transmission for a mobile terminal, wherein

the network element is arranged to establish a tunnel with a mobile terminal for transferring information with the mobile terminal accessing the mobile network via the wireless local network,

5                   **characterized** in that

the network element is arranged to receive a resource authorization identifier from the mobile terminal,

the network element is arranged to request authorization from a signalling element on the basis of the resource authorization identifier,

10                   the network element is arranged to bind a tunnel between the mobile terminal and the mobile network to an end-to-end data flow of the mobile terminal on the basis of an authorization response received from the signalling element and comprising identification information on the end-to-end data flow and tunnel identification information identifying the tunnel.

15

10. A network element according to claim 9, **characterized** in that

the network element is arranged to transmit at least one filter or gate parameter from the signalling element to the mobile network,

20                   the network element is arranged to associate the received at least one filter or gate parameter with the tunnel utilizing local network resources, and

the network element is arranged to arrange filtering or gating in the mobile network to/from the tunnel based on the association.

25

11. A network element according to claim 9 or 10, **characterized** in that

the network element is arranged to use the same tunnel between the mobile network and a network element of the mobile network and utilizing the data transmission resources of the local network for signalling purposes and for user data transmission.

30

12. A network element according to claim 9 or 10, **characterized** in that

35                   the network element is arranged to establish a first tunnel between the mobile terminal and a first network element of the mobile network for the



mobile terminal signalling, and a second tunnel between the mobile terminal and a second network element of the mobile network for user data transmission after the reception of a resource authorization identifier.

5           13. A network element according to any one of claims 9 to 12, **characterized** in that

the tunnel between the mobile terminal and the mobile network is an IPSec tunnel, whereby the tunnel is established by utilizing an IKE (Internet Key Exchange) protocol.

10

14. A network element according to any one of claims 9 to 13, **characterized** in that the network element is a 3GPP network element offering a packet-switched service for a mobile terminal accessing a WLAN (Wireless Local Area Network).

15

15. A wireless terminal arranged to connect a wireless local network, and

the wireless terminal arranged to establish a tunnel with a network element of a mobile network via the wireless local network, **character-**  
20 **ized** in that

the wireless terminal is arranged to receive a resource authorization identifier from a separate signalling element during the negotiation of end-to-end service related parameters, and

the wireless terminal is arranged to transmit the resource authorization identifier to the mobile network by using the tunnel.  
25

16. A computer program product, loadable into the memory of a network element of a mobile network connectable to a wireless local network, for controlling the network element by executing the program code included in  
30 the computer software product in a processor of the network element, **characterized** by the computer program product comprising:

a program code portion for controlling the network element to receive a resource authorization identifier from the mobile terminal,

a program code portion for controlling the network element to  
35 request authorization from a signalling element on the basis of the resource authorization identifier, and

a program code portion for controlling the network element to bind a tunnel between the mobile terminal and the mobile network to an end-to-end data flow of the mobile terminal on the basis of an authorization response received from the signalling element and comprising identification information on the end-to-end data flow and tunnel identification information identifying the tunnel.

17. A computer program product, loadable into the memory of a wireless terminal, for controlling the wireless terminal by executing the program code included in the computer software product in a processor of the wireless terminal, **characterized** by the computer program product comprising:

a program code portion for controlling the wireless terminal to receive a resource authorization identifier from a separate signalling element during the negotiation of end-to-end service related parameters, and

a program code portion for controlling the wireless terminal to transmit the resource authorization identifier to the mobile network by using the tunnel.

**ABSTRACT**

The present invention relates to a method of arranging the transmission of packet data in a system comprising a mobile terminal, a wireless local network and a mobile network. End-to-end service related parameters are signalled via a separate signalling element. A resource authorization identifier is transmitted to the mobile network via the local network. Authorization is requested from the signalling element on the basis of the resource authorization identifier. A tunnel between the mobile terminal and the mobile network is bound to the end-to-end data flow of the mobile terminal on the basis of an authorization from the signalling element and tunnel identification information identifying the tunnel.

(Figure 3)

The diagram illustrates a network architecture for mobile communication. It shows the following components and connections:

- Access Network (AN):** Contains two mobile stations (MS) connected to an Access Point (AP). The AP is connected to a Gateway (GW).
- IP Network (IPNW):** The GW connects to the IPNW, which is also connected to the Internet.
- Public Land Mobile Network (PLMN):** The IPNW connects to the PLMN. Inside the PLMN, there is an Access Server (AS), a WAG, a PDG, a CSCF, and an HLR/HSS. The AS is connected to the WAG and the HLR/HSS. The WAG is connected to the PDG. The PDG is connected to the CSCF and the HLR/HSS. The PLMN also connects to the Internet.

Remote IP					Remote IP	
Tunneling layer					Tunneling layer	L2/L1
Transport IP	Transport IP	Transport IP	Transport IP	Transport IP	Transport IP	
L2/L1	L2/L1	L2/L1	L2/L1	L2/L1	L2/L1	
MS	WLAN AN		WAG		PDG	

FIG. 2

2/2




FIG. 3